



132
203



Victoria

A: 27 Metcalf Street, Dandenong South, Victoria, 3175

P: (03) 9796 3744

Western Australia

A: 260 Allen Road Forrestdale, Western Australia, 6112

P: (08) 9418 4988

Queensland

A: Unit 8, 315 Archerfield Road, Richlands, Queensland, 4077

P: (03) 9796 3744

New South Wales

A: Unit D, 26 Penny Place, Arndell Park, New South Wales, 2148

P: (03) 9796 3744

E: sales@abdexhydraulics.com.au

PNEUMATIC JACKS

YAK 132

Pneumatically controlled jacks consisting of a highly resistant diaphragm and internal telescopic guide.

These jacks are fitted with a limit stop device as well as a safety valve making them absolutely reliable in the case of excessive loads. Silent, simple and lightweight, they are ideal for tyre repairers and bodywork shops in view of the fact they can also be used on column lifts.


YAK 203

Pneumatically controlled jacks consisting of a highly resistant diaphragm and internal telescopic guide.

These jacks are fitted with a limit stop device as well as a safety valve making them absolutely reliable in the case of excessive loads. Silent, simple and lightweight, they are ideal for tyre repairers and bodywork shops in view of the fact they can also be used on column lifts.

SPECIFICATIONS	YAK 132	YAK 203
Capacity	2 t 2.2 ton	2 t 2.2 ton
Net weight	14 kg 31 lb	17 kg 37 lb
Working air pressure	8-10 bar 116-145 psi	8-10 bar 116-145 psi
Air waste	50 nl/min	70 nl/min

Compatible optional accessories can be found on our accessories catalogue.

DIMENSIONS	YAK 132	YAK 203
C	415 mm 16.34 in	415 mm 14.34 in
D	250 mm 9.84 in	250 mm 9.84 in
E	132-326 mm 5.2-12.83 in	205-490 mm 8.07-19.29 in
	2.0 t 2.2 ton	2.0 t 2.2 ton

